

Ordering code

01	02	03	04	05	06	07	08	09	10
Z2FS	6			- 4X	/				*

01	Throttle check valve	Z2FS
02	Size 6	6
03	Throttle check valve side A and B	- ¹⁾
	Throttle check valve side A	A
	Throttle check valve side B	B

Adjustment type

04	Setscrew with lock nut and protective cap (versions "J3" and "J5" without protective cap)	2
	Lockable rotary knob with scale	3 ²⁾
	Spindle with internal hexagon and scale	5
05	Component series 40 ... 49 (40 ... 49: unchanged installation and mounting dimensions)	4X
06	With fine adjustment	1Q
	Standard version	2Q

Corrosion resistance (outside)

07	None (valve housing primed)	no code
	Improved corrosion protection (240 h salt spray test according to EN ISO 9227)	J3 ³⁾
	High corrosion protection (720 h salt spray test according to EN ISO 9227)	J5 ³⁾

Seal material (observe compatibility of seals with hydraulic fluid used, see page 5)

08	NBR seals	no code
	FKM seals	V
09	Without locating hole	no code
	With locating hole	/60 ⁴⁾
10	Further details in the plain text	*

- 1) Identical adjustment types on sides A and B
- 2) H-key with material no. **R900008158** is included in the scope of delivery.
- 3) Only adjustment types "2" and "/60"
- 4) Locking pin ISO 8752-3x8-St, material no. **R90005694** (separate order)

**Notes:**

- ▶ For valve types for use in potentially explosive atmospheres, refer to data sheet 07011.
- ▶ Preferred types and standard units are contained in the EPS (standard price list).